

Card Reader SO-3394



- Reads MIFARE Desfire.
- Keypad.
- Two generations of keys, automatic key upgrade.
- Indoor and outdoor use.
- Software can be updated remotely.
- Certified in Alarm Grade 2 (SSF 1014) and Grade 2 (EN50131-3).

Vandal-resistant card reader in durable plastic with molded electronics and keypad, designed to be placed in exposed environments. The card reader reads contactless MIFARE Desfire cards and can indicate, for example, an open or blocked door using LEDs and buzzer. The SO-3394 can also authenticate the cards and perform sector reading.

The card reader is certified in Alarm Grade 2 (SSF 1014) and Grade 2 (EN50131-3) and can be used to arm and disarm alarms.

Monitored and encrypted two-way communication provides a more secure system.

Card Reader SO-3394

Technical data

Supply voltage:	12 VDC
Card reading technology:	Mifare® 13,56 MHz. ISO 14443A. Desfire EV1, EV2 and EV3. Mifare Plus LV1 and LV3. Mifare Classic. ISO 15693. ICODE
Indication LED's:	3
Buzzer:	Yes
Tamper:	Yes. Tilt Sensor.
Enclosure:	ABS. Molded electronics.
Environment:	Indoors/outdoors (rain cover recommended), IP65.
Environmental class:	EN50130-5. Class IV A. -40° to +70°.
Alarm grade:	EN50131-3. Grade 2. SSF 1014 Alarm Grade 2.
Cable length:	30 meters to Door controller.
Dimensions:	Width 110 mm, Height 145 mm, Depth 23,8 mm, Weight 190 g.
Part number:	SO-3394